



# MARINE BEARING INDUSTRIES, INC.

## PRECISELY MATCHED 2-ROW TAPERED BEARING ASSEMBLIES

Bearing Part Number		bore	outside diameter	width thru cones	width thru cups	snap ring diameter	snap ring width
Cone	Cup	d	D	T	C	D2	f
LM11749	LM11710	0.6875	1.5700	1.190	0.940	1.650	0.100
		17.463	39.878	30.23	23.88	41.91	2.54
LM11949	LM11910	0.7500	1.7810	1.376	1.106	1.843	0.156
		19.050	45.237	34.95	28.09	46.81	3.96
LM11949-2	LM11910	0.7500	1.7810	1.500	1.230	1.843	0.280
		19.050	45.237	38.10	31.24	46.81	7.11
LM12749	LM12711	0.8656	1.8100	1.376	1.106	1.872	0.156
		21.986	45.974	34.95	28.09	47.55	3.96
L44643	L44610	1.0000	1.9800	1.245	0.965	2.078	0.125
		25.400	50.292	31.62	24.51	52.78	3.18
L44649	L44610	1.0625	1.9800	1.245	0.965	2.078	0.125
		26.988	50.292	31.62	24.51	52.78	3.18
LM67048	LM67010	1.2500	2.3280	1.406	1.084	2.406	0.156
		31.750	59.131	35.71	27.53	61.11	3.96
LM48548	LM48510	1.3750	2.5625	1.560	1.240	2.656	0.140
		34.925	65.088	39.62	31.50	67.46	3.56
LM29749	LM29710	1.5000	2.5625	1.560	1.240	2.656	0.140
		38.100	65.088	39.62	31.50	67.46	3.56

\* each bearing set can be ordered to a specific internal clearance for the desired axial bench end play